


Interio



INTERIO FL 2x18W EL



IMPIEGO

Plafoniera sporgente estremamente duttile, facilmente utilizzabile per illuminare locali ad uso civile quali scuole, uffici, banche, o ambienti di lavoro in genere.

CARATTERISTICHE TECNICHE

Corpo in lamiera di acciaio verniciata con polveri epossidiche di colore bianco.
Diffusore in policarbonato antiurto, stabilizzato ai raggi UV, finitura opale.
Testate di chiusura in ABS stabilizzato ai raggi UV.
Alimentazione elettronica 220/250V 50/60Hz; cavo HT 105° non propagante la fiamma; morsettiera 2P+T in nylon fibra di vetro.

APPLICATION

Surface mounting fitting suitable to light up civil use facilities as schools, offices, banks or work environments.

TECHNICAL FEATURES

Housing in steel sheet white epoxy powder painted.
Opal polycarbonate shockproof diffuser, UV stabilized.
ABS UV stabilized closing heads.
Electronic power supply 220/250V 50/60Hz, PVC HT 105° wiring non-flame propagating, nylon with fiber glass 3 poles terminal block.



PLAFONIERE SPORGENTI

Surface Mounting Fittings

INTERIO

CODICE Code	POTENZA Power	ESECUZIONE Execution	PORTALAMPADA Lampholder	COLORE Colour	B	I	PESO KG Weight
606821.118	FL 1x18W T8	EL	2xG13	Bianco/White	635	450	0,80
606821.136	FL 1x36W T8	EL	2xG13	Bianco/White	1240	900	1,20
606821.158	FL 1x58W T8	EL	2xG13	Bianco/White	1540	900	1,60
606821.218	FL 2x18W T8	EL	4xG13	Bianco/White	635	450	1,00
606821.236	FL 2x36W T8	EL	4xG13	Bianco/White	1240	900	1,70
606821.258	FL 2x58W T8	EL	4xG13	Bianco/White	1540	900	2,00

Disponibile a richiesta:

- Kit di emergenza

Available on request:

- Emergency kit

Colori disponibili:

- Bianco



Available colours:

- White

